

## Amazon SE



Professional super elastic (SE) pvc spiral hose, for the suction and delivery of used water. Specially constructed to meet the demands of cleaning trucks. Easy to use, even at low temperatures.

Temperature: -20°C to +60°C

**Constructie:** plasticized grey pvc, reinforced by a concealed white hard pvc spiral, very flexible and smooth on both in- and outside

Security coefficient at 20°C: 3 times the WP

### Applications

Suction and discharge for used water

### Assembly

all types of couplings, assembled with hose clamps

| Reference | Diameter (mm) | Wall thickness (mm) | Weight (g/m) | Bending radius (mm) | Working Pressure (bar) | Vacuum (mH2O) | Coil length (m) |
|-----------|---------------|---------------------|--------------|---------------------|------------------------|---------------|-----------------|
| APSE020   | 20            | 3,5                 | 300          | 125                 | 6                      | 10            | 50              |
| APSE025   | 25            | 3,7                 | 400          | 130                 | 6                      | 10            | 50              |
| APSE030   | 30            | 3,7                 | 550          | 140                 | 6                      | 10            | 50              |
| APSE032   | 32            | 4                   | 610          | 145                 | 6                      | 10            | 50              |
| APSE035   | 35            | 4,2                 | 630          | 150                 | 6                      | 10            | 50              |
| APSE038   | 38            | 4,3                 | 690          | 175                 | 6                      | 10            | 50              |
| APSE040   | 40            | 4,4                 | 720          | 185                 | 6                      | 10            | 50              |
| APSE045   | 45            | 4,5                 | 860          | 200                 | 5,5                    | 10            | 50              |
| APSE050   | 50            | 4,6                 | 1000         | 235                 | 5                      | 10            | 50              |
| APSE055   | 55            | 4,8                 | 1150         | 250                 | 5                      | 9             | 50              |
| APSE060   | 60            | 5                   | 1260         | 280                 | 5                      | 9             | 50              |
| APSE063   | 63            | 5,2                 | 1400         | 300                 | 4,5                    | 9             | 50              |
| APSE070   | 70            | 5,4                 | 1600         | 340                 | 4,5                    | 9             | 50              |
| APSE076   | 76            | 5,5                 | 1720         | 375                 | 4,5                    | 9             | 50              |
| APSE080   | 80            | 6                   | 1860         | 400                 | 4                      | 9             | 50              |
| APSE090   | 90            | 6,3                 | 2100         | 440                 | 4                      | 9             | 50              |
| APSE102   | 102           | 6,6                 | 2700         | 490                 | 3,5                    | 8             | 30 - 50         |
| APSE110   | 110           | 6,9                 | 2950         | 550                 | 3,5                    | 8             | 30              |
| APSE120   | 120           | 7,5                 | 3400         | 610                 | 3                      | 8             | 25              |
| APSE125   | 125           | 7,5                 | 3650         | 650                 | 3                      | 8             | 20              |
| APSE150   | 150           | 8,8                 | 5100         | 780                 | 2                      | 8             | 20              |
| APSE200   | 200           | 12                  | 9600         | 1160                | 1,5                    | 8             | 10              |
| APSEGB063 | 63            | 5,2                 | 1400         | 300                 | 4,5                    | 9             | 50              |
|           | 75            | 5,5                 | 1720         | 375                 | 4,5                    | 9             | 50              |
| APSEGB075 | 90            | 6,3                 | 2100         | 440                 | 4                      | 9             | 50              |



|           |     |     |      |      |     |   |            |
|-----------|-----|-----|------|------|-----|---|------------|
| APSEGB090 | 100 | 6,6 | 2700 | 490  | 3,5 | 8 | 50         |
| APSEGB100 | 125 | 7,5 | 3650 | 650  | 3   | 8 | 4 - 5 - 50 |
| APSEGB125 | 150 | 8,8 | 5100 | 780  | 2   | 8 | 4 - 5 - 50 |
| APSEGB150 | 200 | 12  | 9600 | 1160 | 1,5 | 8 | 10         |
| APSEGB200 |     |     |      |      |     |   |            |

Product ID: 14030

Source URL: <https://www.alfaflex.com/en/products/10000/14000/amazone-se-0>